






XRLED 1500-W Spot

Model: PR-8170A

RoHS | CE |  |  WDMX | LED |  5m |  IP₂₀ | T_c150°C | T_a40°C | 

XRLED 1500-W Spot is a new launched LED spot moving head, equipped with 600W LED module. The unit offers double rotating gobo wheels, colorful prism, wide range beam light, combined with touch screen, network interface, intelligent fan control, automatic focusing, sensor fault diagnosis, etc.




600W LED, spot



Rotating gobos(Ø37.5mm, image Ø26mm)



Scan with your Phone
to view more detail



42Kg
Size(mm)

Specifications

- Input Voltages
100-240V AC, 50/60Hz
- Power Consumption
880W@220V, 930W@100V
- Light Source
600W white LED(8,000K), 20,000 hrs
- Strobe
Electronic strobe, 0.3-25 F.P.S
- Dimmer
0-100% linear adjustment
Four kinds of optional dimmer modes
- Colors
CMY linear color mixing with macros
1 Color wheel: 6 dichroic color filters plus open
Half color effect, variable speed rainbow effect
Stepping/linear color changing is optional
0-100% linear color temperature adjustment
- CTO
0-100% linear CTO system
- Gobos
2 Rotating gobo wheels: each with 6 replaceable gobos plus open, glass or metal gobos can be fixed
Bi-directionally rotatable and wheel scrolling at variable speed, indexable
Shakable at variable speeds
- Prism
One 4-facet prism, bi-directionally rotatable at variable speed, indexable
- Effect
1 Replaceable animation wheel, bi-directionally rotatable at variable speed
- Iris
5-100% linearly adjusted with macros
- Focus
Motorized linear focus
- Zoom
Motorized linear zoom
- Head Movement
Pan 540°, tilt 270° with auto position correction
Swap and invert functions of pan and tilt
- Light Angle
6°~56°
- Control
International DMX512, 5 pins(optional: 3 pins) interface
Short mode 25 channels, standard mode 31 channels, and extended mode 38 channels
RDM protocol
Art Net protocol
Master-slave mode, stand-alone mode, self-test mode
- Other Functions
Adjustable pan & tilt speed
Touch panel display in English, and its brightness and contrast adjustable
Fixture and lamp usage time display
Built-in analyzer for easy fault finding, error messages
Setup options by chargeable battery inside without power connection
Software version display
Modular structure easy for maintenance
Network interface
DMX512 wireless receiver
DMX512 wireless transmitter(optional)
- Weight
Net weight: 42kg

- Physical
Housing: composite plastic, IP20
Ambient working temperature: maximum 40°C
- Packaging
Standard: carton 860x655x815(mm)
Optional: flight case N/A
- Accessories
G clamp, 2 pcs
5 pins XLR connector, 1 set
Safety cord, 2 pcs
Optional: Ω clamp, 2 pcs

