## **CUBIX 300**

**RoHS**  $|\mathbf{C}\mathbf{E}|$  LED  $(-1.5\text{m}] |\mathbf{R}| |\mathsf{R}| |\mathsf{T}_{c} |\mathsf{150}^{\circ} \mathsf{C}| |\mathsf{T}_{a} |\mathsf{40}^{\circ} \mathsf{C}| |\underline{\mathbb{Z}}|$ 

Model: PR-6803

CUBIX 300 is a new launched exterior gobo projector, equipped with a 150W bright white LED source. With precise control, 15°~45° wide zoom, small and light weight.

IP65, Gobo effect







Scan with your Phone to view more detail







## Specifications

- Input Voltages 100V~240V AC.50/60Hz
- Power Consumption 170W@230V
- Light Source 150W LED white(7,500k), 50,000 hrs
- Strobe
  Electronic strobe, 0-25 F.P.S(preset pulse strobe effect)
- Dimmer 0-100% linear adjustment
- Colors
   1 Color wheel: 5 dichroic color filters plus open Continual rotation, magnet sensor positioning
- Gobo 1 Rotating gobo wheel: 4 gobos
- Light Angle Field angle: 15°~45°
- Control
   International DMX512, 3 pins(optional 5 pins) interface
   Master-slave synchronized mode, stand-alone mode, preset mode, test mode, and single scene mode

DMX mode, preset memories and user memory mode

■ Other Functions
LCD panel
Over temperature protection
Fast and convenient software upgrade via DMX512 interface
Built in NTC temperature detecting function, If LED lamp is
over heat, its power will be decreased intelligently
DMX 512 wireless receiver(optional)
DMX 512 wireless transmitter(optional)

- Physical Housing: high-intensity die-casting aluminum, IP65 Ambient working temperature: -20°C~40°C
- Weight Net weight: 9.5kg
- Packaging Standard: carton 340x335x440(mm) Optional: flight case N/A
- Accessories
  C clamp, 1 pc
  Signal adapter cord, 2 pcs
  Power cord, 1 pc
  Safety cord, 1 pc
  Optional: transparent cover+seal+screws x6, 1set



