
## LS 150/90 Water

Model: PR-6810/6809



locations.

IP65, Water Effect





Scan with your Phone to view more detail







7.5Kg Size(mm)

## Specifications

- Input Voltages 100V~240V AC,50/60Hz
- Power Consumption
  LS 150 Water(PR-6810):300W@230V
  LS 90 Water(PR-6809): 130W@230V
- Light Source LS 150 Water(PR-6810):150W LED white(7,500k), 50,000 hrs LS 90 Water(PR-6809): 90W LED white(7,500k), 50,000 hrs
- Strobe Electronic strobe, 0-25 F.P.S(preset pulse strobe effect)
- Dimmer 0-100% linear adjustment
- Colors
   1 Color wheel: 5 dichroic color filters plus open Continual rotation, magnet sensor positioning
- Effect
  2 Water effect wheels, independently and bi-directionally continually rotating
- Light Angle Field angle: 45°
- Control
   International DMX512, 3 pins and 5 pins interface
   Master-slave synchronized mode, stand-alone mode, preset mode, test mode, and single scene mode
   DMX mode, preset memories and user memory mode
- Other Functions
  LCD panel
  Over temperature protection
  Fast and convenient software upgrade via DMX512 interface
  Built in NTC temperature detecting function, If LED lamp is
  over heat, its power will be decreased intelligently

- Physical Housing: high-intensity die-casting aluminum, IP65
- Weight Net weight: 7.5kg
- Packaging
  Standard: carton 585x345x310(mm)
  Optional: flight case 940x465x573(mm), 6 in 1

Ambient working temperature: -20°C~45°C

■ Accessories
C clamp, 1 pc
Signal adapter cord, 2 pcs
Power cord, 1 pc
Safety cord, 1 pc
Optional: transparent cover+seal+screws x6, 1set



